

T E S T C E R T I F I C A T E

ST-26-02-17-12

Product: Laminate floor covering of assembly group 34: Kaindl laminate floor covering Classic Touch 8.0 mm
Producer: Kaindl Flooring GmbH, Kaindlstrasse 2, 5071 Wals/ Salzburg, Austria
Order: Carry out of an external quality control on laminate floor coverings according to EN 13329:2023, ISO 14486:2025 and on other selected properties
Test reports: 2117129/2025/2, 5/5W/5W1/9, 12 and quarterly reports of CARB/EPA surveillance

Test results:

Properties	Results of classification requirements tests according to EN 13329: 2023/ ISO 14486:2025 / other tests	
Abrasion resistance	AC4	
Impact resistance	Small ball	≥ 35 mm
	Big ball	≥ 750 mm
Resistance against staining	Groups 1 und 2	Grade 5
	Group 3	Grade 4
Effect of a furniture leg	no visible damages	
Effect of a castor chair	no visible damages	
Thickness swelling	≤ 18 %	
Locking strength	f _{10,2} ≥ 1 kN/m / f _{50,2} ≥ 2 kN/m	
Surface soundness	≥ 1,25 N/mm ²	
PCP/Lindane	< 5 ppm	
Formaldehyde release according to EN ISO 12460-3	Austrian formaldehyde ordinance are fulfilled	
Formaldehyde emission according to EN 717-1	Requirements FA-REACH-2026 ¹ / ChemVerbotsV-2020 ² fulfilled	
Formaldehyde requirements of CARB Phase 2 and EPA TSCA Title VI.	Carrier boards certified by TPC 10	
Content of heavy metals, chromium VI and organostannic compounds according to EN 71-3	Requirements fulfilled	
VOC-Emission according to EN 16516	Requirements of AgBB-scheme and MVVTB ABG annex 8, French Class A+, BREEAM General Level; Belgian VOC regulation; Finnish M1 classification, LEED v4 and TÜV PROFICERT-product Interior PREMIUM are fulfilled	

¹ Formaldehyde emission limit value according to COMMISSION REGULATION (EU) 2023/1464 of 14 July 2023 amending Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council as regards formaldehyde and formaldehyde releasers, Formaldehyde limit value 0.062 mg/m³ for furniture and wood-based products.

² Limit value for formaldehyde emissions in accordance with the Chemicals Prohibition Ordinance (ChemVerbotsV) Annex 1 to §3 of 20.01.2017 in conjunction with the announcement of analytical methods published on November 26, 2018, BAnz AI 26.11.2018 B2, 124 µg/m³ (0.1 ppm)


The tested laminate floor covering meets all requirements according to EN 13329: 2023 and ISO 14486:2025 for the class 32.

This test certificate is valid until 16/02/2027.

Dresden, 17/02/2026



Head of laboratory

Engineer in charge